

Continuous Duty Rating - P1									
Rating Mhp (kW)	Engine model	Cyl.	Cubic capacity, litres	Rpm	Dry weight, kg	Fuel injection (mech or elec)	Length, mm	Width, mm	Height, mm
400 (294)	6 W126M	6	11.6L	1800	1200	m	1695	883	1128
450 (331)	6 M26.2	6	15.9L	1800	1985	m	1880	1144	1348
500 (368)	6 M26.2	6	15.9L	1800	1985	m	1880	1144	1348
600 (441)	6 M26.3	6	15.9L	1800	1985	e	2034	1078	1239
600 (441)	8 M26.2	8 V	21.2L	1800	2475	m	1871	1392	1454
650 (478)	6 M33.2	6	19.6L	1800	2390	m	1870	1138	1417
668 (491)	8 M26.2	8 V	21.2L	1800	2475	m	1871	1392	1454
700 (515)	6 M33.2	6	19.6L	1800	2390	m	1870	1138	1417
900 (662)	12 M26.2	12 V	31.8L	1800	3400	m	2446	1355	1419
1000 (736)	12 M26.2	12 V	31.8L	1800	3400	m	2446	1355	1419
1200 (883)	12 M26.3	12 V	31.8L	1800	3215	e	2333	1350	1494
1300 (956)	12 M33.2	12 V	39.2L	1800	3900	m	2210	1467	1568
1400 (1029)	12 M33.2	12 V	39.2L	1800	3900	m	2210	1467	1568
Heavy Duty Rating - P2									
130 (95)	4 W105M	4	4.5L	2100	650	m	985	821	650
185 (136)	6 W105M	6	6.7L	2100	810	m	1417	885	1076
360 (264)	6 M16	6	9.7L	2100	1056	m	1514	878	1381
450 (331)	6 W126M	6	11.6L	2100	1200	m	1695	883	1128
550 (404)	6 M26.2	6	15.9L	1900	1985	m	1880	1144	1348
600 (442)	6 M26.2	6	15.9L	1900	1985	m	1880	1144	1348
660 (485)	6 M26.3	6	15.9L	1800	1985	e	2034	1078	1239
700 (515)	6 M26.3	6	15.9L	2000	1985	e	2034	1078	1239
733 (539)	8 M26.2	8 V	21.2L	1900	2475	m	1871	1392	1454
750 (551)	6 M26.3	6	15.9L	2100	1985	e	2034	1078	1239
750 (551)	6 M33.2	6	19.6L	1800	2390	m	1870	1138	1417
800 (588)	8 M26.2	8 V	21.2L	1950	2475	m	1871	1392	1454
1100 (808)	12 M26.2	12 V	31.8L	1900	3400	m	2446	1355	1419
1200 (883)	12 M26.2	12 V	31.8L	1950	3400	m	2446	1355	1419
1320 (970)	12 M26.3	12 V	31.8L	1800	3215	e	2333	1350	1494
1400 (1030)	12 M26.3	12 V	31.8L	2100	3215	e	2333	1350	1494
1500 (1104)	12 M26.3	12 V	31.8L	2200	3215	e	2333	1350	1494
1500 (1104)	12 M33.2	12 V	39.2L	1800	3900	m	2210	1467	1568
Intermittent Duty Rating - P3									
228 (168)	6 W105M	6	6.7L	2450	810	m	1417	885	1076
550 (404)	6 M26.3	6	15.9L	2100	1985	e	2034	1078	1239
1650 (1214)	12 M26.3	12 V	31.8L	2300	3215	e	2333	1350	1494
Light Duty Rating - P4									
252 (185)	6 W105M	6	6.7L	2500	810	m	1417	885	1076

5000+ hrs pa
 80 - 100% load factor
 Unrestricted continuous with full load
 Trawlers, tugs, dredgers, deck container ships

3000 - 5000 hrs pa
 30 - 80% load factor
 Continuous with full load variations
 Tugs, fishing, freight and working ships

1000 - 3000 hrs pa
 50% load factor
 Intermittent with important load variation
 Ferries, fishing boats, commercial or pleasure

Under 1000 hrs pa
 30% load factor
 High importance, very important load variations
 Fast patrol boats, sea rescue, pleasure craft